



❗ Discontinued

Commercial status

Discontinued on: 31 December 2016

End-of-service on: 31 December 2016

PM870MG has not been replaced. Please contact your customer care center for more information.

Main

Range of product	PowerLogic PM800
Device short name	PM870
Product or component type	Power meter

Complementary

Power quality analysis	Up to the 63rd harmonic
Type of measurement	Current Voltage Frequency Power factor total Apparent power total Active power total Reactive power total Apparent power per phase Active power per phase Reactive power per phase Energy Power factor per phase
Supply voltage	125...250 V DC 115...415 V AC 45...67 Hz 115...415 V AC 350...450 Hz
Network frequency	45...67 Hz 350...450 Hz
Maximum power consumption in VA	15 VA
Display type	Backlit LCD
Display resolution	6 lines
Sampling rate	128 samples/cycle
Measurement current	1 A 5 A
Input type	Current 0.005...10 A (impedance ≤ 0.1 Ohm)
Measurement voltage	0...600 V AC phase to phase 0...347 V AC phase to neutral

Number of inputs	1 digital 0...5 mA 24...125 V AC/DC
Measurement accuracy	Current 0.5 % 0.5...10 A Voltage 0.2 % 10...227 V Energy 0.2 % Frequency 0.01 Hz Power factor 0.002 Power 0.2 %
Accuracy class	Class 2 reactive energy conforming to IEC 62053-23 Class 0.5S active energy conforming to IEC 62053-22 Class 0.2 active energy conforming to ANSI C12.20
Number of outputs	1 digital (static)
Communication port protocol	Modbus 38.4 kbauds
Communication port support	RS485
Data recording	GPS synchronisation Trending/forecasting 4 data logs and PQ sag/swell Event logs Time stamping Alarms Min/max of instantaneous values
Memory capacity	800 kB

Environment

Electromagnetic compatibility	Immunity to impulse waves: , conforming to IEC 61000-4-12 Limits for harmonic current emissions: , conforming to IEC 61000-3-2 Conducted and radiated emissions: , conforming to EN 55011 class A Electrostatic discharge immunity test: , class III, conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields: , class III, conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test: , class III, conforming to IEC 61000-4-4 1.2/50 µs shock waves immunity test: , class III, conforming to IEC 61000-4-5 Conducted RF disturbances: , class III, conforming to IEC 61000-4-6 Immunity to impulse waves: , class III, conforming to IEC 61000-4-8 Immunity to microbreaks and voltage drops: , class III, conforming to IEC 61000-4-11 Limitation of voltage changes, voltage fluctuations and flicker in low-voltage: , conforming to IEC 61000-3-3
Mounting mode	Flush-mounted
Mounting support	Panel
Type of installation	Indoor installation
Overvoltage category	III
IP degree of protection	IP30 back: conforming to IEC 60529 IP52 front face: conforming to IEC 60529
Relative humidity	90 % at 40 °C
Pollution degree	2
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Operating altitude	0...3000 m
Standards	CSA C22.2 No 14 UL 508 IEC 61010-1
Product certifications	CE CULus
Width	96 mm
Depth	70 mm
Height	96 mm
Net weight	0.6 kg

Packing Units

Package 1 Weight	0.884 kg
Package 1 Height	1.320 dm
Package 1 width	1.220 dm
Package 1 Length	2.770 dm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------