

# Product data sheet

Specifications



## Butterfly Valve, 50 mm, 2-Way, Flanged, Lug, 316 SS, 115 kvs

VF208W-50NS

### Main

Product or component type	Valve
Valve type	Butterfly
Valve product series	VF208W
Valve model	VF208W-50NS 115E B00
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	2-Way
Valve connection type	Flanged
Body size	50 mm (2 in)
Pipe size	50 mm
Flow characteristic	Uncharacterized
Flow coefficient	132.97 cv 115 kvs
Pressure class	PN16
Operating fluid temperature	-10...100 °C
Pressure fluid max delta P normal life	599.84 kPa
Seat leakage	Port A: Class IV-S1 (0.005 %)
Stem movement	Rotary
Disc shape	Full
Disc material	Stainless steel 316
Body material	Nodular cast iron EN-JS 1030
Material seal	EPDM (ethylene propylene diene monomer)
Stem material	Stainless steel AISI 420
Targeted region	Europe Asia Pacific. Australia.

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

---

<b>Package 1 Weight</b>	2.15 kg
<b>Package 1 Height</b>	8.89 cm
<b>Package 1 width</b>	26.67 cm
<b>Package 1 Length</b>	19.05 cm

---

## Offer Sustainability

---

<b>EU RoHS Directive</b>	Not applicable, out of EU RoHS legal scope
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>

---