Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Modicon Momentum - Ethernet communication adaptor - 10 Mbit/s

170ENT11002

Main

| Range of product | Modicon Momentum automation platform |
|-----------------------------|---------------------------------------|
| Product or component type | Ethernet TCP/IP communication adaptor |
| Communication port protocol | Ethernet TCP/IP |
| Method of access | Peer to peer Master/slave |
| Transmission rate | 10 Mbit/s |
| Transmission support medium | Shielded twisted pairs cable |

Complementary

| , | |
|--|--|
| Module configuration | BOOTP server to assign IP parameters |
| Topology | Multidrop, star network |
| Port Ethernet | 10BASE-T |
| Number of devices per segment | 032 |
| Maximum cable distance between devices | 1000 m without repeater |
| Addressing | Unique IEEE global address IP address user assigned |
| Fail state | Fail safe |
| Control parameter | CRC-32 |
| Supply | From I/O base |
| Marking | CE |
| Local signalling | 1 LED (green) for Ethernet network state (LAN) 1 LED (green) for module active (RUN) |
| Electrical connection | 1 connector RJ45 for 10BASE-TX |
| Net weight | 0.07 kg |

Environment

| Product certifications | UL FM Class 1 Division 2 CSA |
|-------------------------|------------------------------------|
| Standards | CSA FM Class 1 Division 2 |
| IP degree of protection | IP20 |

| Protective treatment | тс |
|---------------------------------------|---|
| Resistance to electrostatic discharge | 4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2 |
| Resistance to electromagnetic fields | 10 V/m 801000 MHz conforming to IEC 801-3 |
| Ambient air temperature for operation | 060 °C |
| Ambient air temperature for storage | -4085 °C |
| Relative humidity | 95 % without condensation |
| Operating altitude | <= 5000 m |
| Packing Units | |
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.800 cm |
| Package 1 Width | 17.800 cm |
| Package 1 Length | 26.000 cm |
| Package 1 Weight | 219.000 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 8 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 2.260 kg |
| Offer Sustainability | |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration |
| RoHS exemption information | Yes |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more

Contractual warranty

California proposition 65

Warranty 18 months

Recommended replacement(s)

information go to www.P65Warnings.ca.gov