

# Product data sheet

Specifications



## Automation server, SpaceLogic, AS-P, LonWorks, 2 RS-485 ports, 2 10/100 ethernet ports

SXWASPXXX10001

### Main

<b>Communication service</b>	SNMP network management SMTP e-mail notification SMTPS e-mail notification Modbus TCP client Modbus TCP server
<b>Flame retardance</b>	UL94V0-5VB
<b>Current consumption</b>	400 mA
<b>Product certifications</b>	BTL CE cULus FCC part 15 class B ICES-003
<b>Width</b>	90 mm
<b>Device short name</b>	AS-P
<b>Product or component type</b>	Controller
<b>Net weight</b>	321 g
<b>Height</b>	114 mm
<b>Depth</b>	64 mm
<b>Ambient air temperature for operation</b>	0...50 °C
<b>IP degree of protection</b>	IP20
<b>Ambient air temperature for storage</b>	-20...70 °C
<b>Standards</b>	UL 94 UL 916 FCC CFR 47 part 15
<b>Memory type</b>	512 MB RAM 4 GB flash
<b>Product brand</b>	Schneider Electric
<b>Range</b>	EcoStruxure Building Operation

### Complementary

<b>Material</b>	ABS/PC
<b>Product mounting</b>	On base DIN rail
<b>Web services</b>	TLS 1.0 HTTP server Programmable scripts : alarm summaries, report management

<b>I/O limit processor capacity</b>	464 I/O, 29 modules
<b>Range compatibility</b>	EcoStruxure Building Operation TB-ASP-W1 terminal base EcoStruxure Building Operation TB-AS-W1 terminal base
<b>Processor name</b>	Spear 320s
<b>Communication port protocol</b>	BACnet Modbus TCP master RS485 Modbus TCP slave RS485 HTTPS RJ45 HTTP RJ45 LON TP/FT-10
<b>Integrated connection type</b>	USB 2.0 type A USB type mini B

## Environment

<b>Relative humidity</b>	0...95 %
--------------------------	----------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	11.7 cm
<b>Package 1 Width</b>	5.7 cm
<b>Package 1 Length</b>	9.1 cm
<b>Package 1 Weight</b>	271.0 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	36
<b>Package 2 Height</b>	30.0 cm
<b>Package 2 Width</b>	30.0 cm
<b>Package 2 Length</b>	40.0 cm
<b>Package 2 Weight</b>	10.513 kg

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a>
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>PVC free</b>	Yes
<b>Halogen content performance</b>	Halogen free plastic parts & cables product
<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Recommended replacement(s)