

# Product data sheet

Specifications



## Central I/O module, SpaceLogic, 8 universal inputs, 4 digital Form C outputs

SXWUI8D4X10001

**!** To be discontinued on: 30 April 2024

**!** To be discontinued

### Main

Device short name	UI-8/DO-FC-4
Product or component type	I/O module
Net weight	181 g
Flame retardance	UL94V0-5VB
Height	114 mm
Product certifications	ICES-003 FCC part 15 class B CE RCM
Width	30 mm
Power consumption in VA	1.9 W
Depth	64 mm
Ambient air temperature for operation	0...50 °C
IP degree of protection	IP20
Ambient air temperature for storage	-20...70 °C
Input/Output type	universal input
Relative humidity	0...95 % non-condensing
Product name	I/O Modules
Product brand	Schneider Electric
Range	EcoStruxure Building Operation

### Complementary

Control type	Without
Product compatibility	Honeywell Xenta Continuum Satchwell Johnson Control I/NET Balco
Electrical connection	Plug-in sub-base
Switching frequency	25 Hz

Discrete output number	4
Discrete input number	8
Discrete input voltage	24 V
Discrete output type	Relay
Mounting support	Wall DIN rail
Analogue input type	Configurable voltage, current or probe 0...20 mA Configurable voltage, current or probe 0...10 V input voltage Configurable voltage, current or probe 20 kOhm connection of probes Configurable voltage, current or probe 10 kOhm connection of probes Configurable voltage, current or probe 2.2 kOhm connection of probes Configurable voltage, current or probe 1.8 kOhm connection of probes Configurable voltage, current or probe 1 kOhm connection of probes Configurable voltage, current or probe 10 kOhm with shunt
Local signalling	LED (green/red) for high signal level LED (green/red) for low signal level
Range compatibility	EcoStruxure Building Operation TB-IO-W1 terminal base
Standards	UL 864 UL 916 FCC CFR 47 part 15
Material	ABS + PC

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.6 cm
Package 1 Width	11.7 cm
Package 1 Length	9.1 cm
Package 1 Weight	205.2 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Recommended replacement(s)