

Toote infoleht

Tehnilised andmed



Carbon monoxide detector, Intellia EDI-60

FFS06720260

Main

| | |
|---------------------------|---|
| Range of product | Esmi addressable components for ALC range |
| Product or component type | Carbon monoxide detector |
| Detection type | Carbon monoxide |

Complementary

| | |
|--------------------------------|---|
| [Ue] rated operational voltage | 17...28 V DC polarity sensitive |
| Current consumption | 500 μ A at 24 V DC standby 750 μ A at 24 V DC standby peak 3.5 mA at 24 V DC alarm LED on 1 mA at 24 V DC power-up surge 5 mA at 24 V DC remote LED |
| Material | Body PC (polycarbonate) FR Terminal nickel plated stainless steel |
| Operating altitude | < 2000 m |
| Local signalling | 2 LED red) alarm |
| Output type | Remote LED optional |
| Colour | white |
| Diameter | 100 mm |
| Height | 42 mm |
| Product weight | 105 g |

Environment

| | |
|---------------------------------------|---|
| IP degree of protection | IP44 |
| Relative humidity | 15...90 % non-condensing |
| Ambient air temperature for operation | 0...50 °C continuous -20...55 °C transient |
| Ambient air temperature for storage | -10...30 °C continuous -40...55 °C transient |

Pakke osad

| | |
|------------------------|--------|
| Pakendi tüüp 1 | PCE |
| Ühikute arv pakendis 1 | 1 |
| Package 1 Height | 5,0 cm |

| | |
|------------------|---------|
| Pakendi laius 1 | 12,5 cm |
| Pakendi pikkus 1 | 12,5 cm |
| Pakendi kaal 1 | 250,0 g |

Offer Sustainability

| | |
|-----------------------------|--|
| Jätksuutliku pakkumise olek | Green Premium toode |
| REACH-määrus | REACH-deklaratsioon |
| ELi RoHS direktiiv | Vastavus ELi RoHS deklaratsioon |
| Elavhõbedavaba | Jah |
| Hiina EoHS regulatsioon | Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks. |
| RoHS eranditeave | Jah |
| Keskkonnaalane avaldus | Toote keskkonnaprofiil |
| Ringlusprofiil | Kasutuselt kõrvaldamise teave |

Soovitatud asendus(ed)