





Multi-criteria detector, Intellia EDI-30, smoke, heat

FFS06720230

Main

Range Of Produc	Esmi addressable components for ALC range	
Product Or Component Type	Multisensor detector	
Detection Type	Smoke Heat	

Complementary

[Ue] Rated Operational Voltage	1728 V DC polarity insensitive		
Current Consumption	400 µA at 24 V DC standby 3.5 mA at 24 V DC alarm LED on 1 mA at 24 V DC power-up surge 5 mA at 24 V DC remote LED		
Material	Body: PC (polycarbonate) FR Terminal: nickel plated stainless steel		
Local Signalling	2 LED (red) for alarm		
Output Type	Remote LED optional		
Colour	White		
Diameter	100 mm		
Height	50 mm		
Product Weight	105 g		

Environment

Standards	EN 54-5 EN 54-7
Product Certifications	CPR LPCB
Ip Degree Of Protection	IP44
Relative Humidity	095 % non-condensing
Ambient Air Temperature For Operation	-4070 °C
Ambient Air Temperature For Storage	-4080 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	12.5 cm

Package 1 Length	12.5 cm	
Package 1 Weight	250.0 g	



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration	
Eu Rohs Directive	Compliant with Exemptions	
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	