

MWS3A-KNX | Adjustable head, flush mounted, ceiling, microwave presence/absence detectors, KNX



Unlike fixed head microwave presence detectors the MW3SA-KNX offers a unique presence/absence detection capability by using an adjustable head. This incorporates an innovative locking mechanism to prevent tampering.


Key Product Features:


- Range up to 23m at 2.6m mounting height
- Two ELV switch inputs to manually override the dimming levels and / or override the lights on or off
- KNX programming mode accessible with IR handset and also by using the push switch on the back of the unit
- Programmable logic block. This allows conditions to be set.
 For example: send the occupancy telegram only if the switch is pressed and the lux is low
- All functionality is fully programmable using the KNX ETS commissioning software
- 5 year warranty included.




Detection pattern










Dimensions (mm)



Technical Data

Part Code	MWS3A-KNX
Control method	KNX
IP rating	40
Weight (kg)	0.15
Supply voltage (DC)	30 VDC over KNX bus
Terminal capacity	KNX: 1.2mm² over KNX connector Switch input: 2.5mm²
Working temperature range (°C)	-10 to 35
Humidity	5 to 95% non-condensing
Material (casing)	Flame retardant ABS and PC/ABS
Insulation class	Class 2
Compliance	EMC-2004/108/EC, LVD-2006/95/EC
Purpose	Sensing control
Installation	Independent flush mounted, electronic control



CP Electronics A Business unit of Legrand Electric Limited, Brent Crescent, London NW10 7XR, UK t. +44 (0)333 900 0671 info@cpelectronics.co.uk

www.cpelectronics.co.uk

connect with us 🗾 in 📑 🛗





Important notice:

This device should be installed by a qualified electrician in accordance with the latest edition of the IEE Wiring Regulations and the applicable Building Regulations.

 $\label{eq:decomposition} \mbox{Due to our policy of continual product improvement}$ CP Electronics reserves the right to alter the specification of this product without prior notice.



