

Product datasheet

Specifications



Base sounder beacon, ESI-60, addressable

FFS06728060

Main

Range Of Product	Esmi addressable components for ALC range
Product Or Component Type	Mounting base

Complementary

Product Destination	Audible visual alarm
Colour Tint	Body: white
Device Composition	body in PC (polycarbonate) contacts in stainless steel
[Ue] Rated Operational Voltage	17...28 V DC polarity sensitive
Current Consumption	300 μ A at 24 V DC standby 8 mA at 24 V DC alarm 1.2 mA at 24 V DC power-up surge < 1 s
Local Signalling	LED red flashing at 1 Hz: alarm
Diameter	115 mm
Height	38 mm
Net Weight	160 g

Environment

Standards	EN 54-3 EN 54-17
Product Certifications	LPCB CPR
Ip Degree Of Protection	IP21C
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature For Operation	-20...60 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	12.5 cm
Package 1 Length	12.5 cm
Package 1 Weight	250.0 g

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.


Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
