Product data sheet

Specifications





Central I/O module, SpaceLogic, 16 RTD/digital inputs

SXWRTD16X10001

Product availability: Stock - Normally stocked in distribution facility

Main

Device Short Name	RTD-DI-16
Product Or Component Type	I/O module
Net Weight	5.15 oz (146 g)
Flame Retardance	UL94V0-5VB
Height	4.49 in (114 mm)
Product Certifications	ICES-003 FCC part 15 class B CE RCM
Width	1.18 in (30 mm)
Power Consumption In Va	1.6 W
Depth	2.52 in (64 mm)
Ambient Air Temperature For Operation	32122 °F (050 °C)
Ip Degree Of Protection	IP20
Ambient Air Temperature For Storage	-4158 °F (-2070 °C)
Input/Output Type	digital input
Relative Humidity	095 % non-condensing
Product Name	I/O Modules
Product Brand	Schneider Electric
Range	EcoStruxure Building Operation

Complementary

Control Type	Without	
Electrical Connection	Plug-in sub-base	
Switching Frequency	25 Hz	
Discrete Input Number	16	
Discrete Input Voltage	24 V	
Mounting Support	Wall DIN rail	
Local Signalling	LED green/red) high signal level LED green/red) low signal level	
Range Compatibility	EcoStruxure Building Operation TB-IO-W1 terminal base	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Material	FCC CFR 47 part 15 ABS + PC	
	UL 916	
Standards	UL 864	

ABS + PC

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA	
Discount Schedule	BMS1	
Gtin	7332552010446	
Returnability	No	
Country Of Origin	SE	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.54 in (9.0 cm)
Package 1 Width	2.24 in (5.7 cm)
Package 1 Length	4.65 in (11.8 cm)
Package 1 Weight	6.11 oz (173.2 g)

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
 Rohs Exemption Information Yes
 Pvc Free
 Halogen Free Plastic Parts & Cables Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov