

Product data sheet

Specifications



Central I/O module, SpaceLogic, 8 universal inputs, 4 analog outputs

SXWUI8A4X10001

⚠ To be discontinued on: Apr 30, 2024

⚠ To be discontinued

Product availability: Stock - Normally stocked in distribution facility

Main

Device Short Name	UI-8/AO-4
Product Or Component Type	I/O module
Net Weight	5.36 oz (152 g)
Flame Retardance	UL94V0-5VB
Height	4.49 in (114 mm)
Product Certifications	ICES-003 FCC part 15 class B CE RCM UL
Width	3.54 in (90 mm)
Depth	2.52 in (64 mm)
Ambient Air Temperature For Operation	32...122 °F (0...50 °C)
Ip Degree Of Protection	IP20
Ambient Air Temperature For Storage	-4...158 °F (-20...70 °C)
Power Consumption In W	3.2 W
Input/Output Type	universal input
Relative Humidity	0...95 % non-condensing
Number Of Outputs	4 analog output
[Us] Rated Supply Voltage	24 V DC
Product Name	I/O Modules
Product Brand	Schneider Electric
Range	EcoStruxure Building Operation

Complementary

Control Type	Without
Product Compatibility	Johnson Control Xenta Balco Continuum Honeywell I/NET Satchwell
Electrical Connection	Plug-in sub-base
Switching Frequency	25 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discrete Input Number	8
Mounting Support	DIN rail Wall
Analogue Input Type	Configurable voltage, current or probe 0...20 mA Configurable voltage, current or probe 0...10 V input voltage Configurable voltage, current or probe 20 kOhm connection of probes Configurable voltage, current or probe 10 kOhm connection of probes Configurable voltage, current or probe 2.2 kOhm connection of probes Configurable voltage, current or probe 1.8 kOhm connection of probes Configurable voltage, current or probe 1 kOhm connection of probes Configurable voltage, current or probe 10 kOhm with shunt
Local Signalling	LED green/red) high signal level LED green/red) low signal level
Range Compatibility	EcoStruxure Building Operation TB-IO-W1 terminal base
Standards	UL 864 UL 916 FCC CFR47 part 15
Material	ABS + PC

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
Gtin	7332552009747
Returnability	No
Country Of Origin	SE

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.20 in (5.6 cm)
Package 1 Width	4.61 in (11.7 cm)
Package 1 Length	3.58 in (9.1 cm)
Package 1 Weight	6.00 oz (170.0 g)

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Pvc Free

Halogen Free Plastic Parts & Cables Product

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)

California Proposition 65 WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov