

Product data sheet

Specifications



STP Series immersion temperature sensor, STP300-100 0/100, pipe, 100 mm probe, 2-Wire, 0-100 °C

006920241

Main

| | |
|---------------------------------------|-------------------------------------|
| Range Of Product | STP300 |
| Product Or Component Type | Sensor |
| Type Of Measurement | Temperature |
| Device Application | Pipe immersion |
| Analogue Output Type | 4...20 mA |
| Ip Degree Of Protection | IP65 |
| Location | Plant room |
| Mounting Support | Pipe |
| Depth | 45 mm |
| Height | 85 mm |
| Net Weight | 0.107 kg |
| Width | 65 mm |
| Output Type | Analog output |
| Standards | EN 50082-1 EN 50081-1 |
| Colour | Black and green |
| Ambient Air Temperature For Operation | -10...150 °C |
| Sensor Type | Temperature transmitter temperature |
| Targeted Region | Asia Pacific. Europe |

Complementary

| | |
|---------------------------|--|
| Type Of Installation | Immersion |
| Material | PA (polyamide): connection box Stainless steel: immersion tube |
| Time Constant | 19000 ms brass PN 16 with contact paste 20000 ms stainless steel PN 25 with contact paste 23000 ms brass PN 16 without contact paste 24000 ms stainless steel PN 25 without contact paste |
| [Us] Rated Supply Voltage | 15...36 V AC |
| Connections - Terminals | Wire (AWG 24...AWG 18) |
| Length | 100 mm |
| Diameter | 6 mm probe: |
| Number Of Cables | 1 <1 m |

| | |
|----------------------|----------------------|
| Measurement Accuracy | 0...25 °C +/- 0.3 °C |
|----------------------|----------------------|

Environment

| | |
|------------------------|----|
| Product Certifications | CE |
|------------------------|----|

| | |
|-------------------|------------|
| Measurement Range | 0...100 °C |
|-------------------|------------|

Packing Units

| | |
|------------------------|-----|
| Unit Type Of Package 1 | PCE |
|------------------------|-----|

| | |
|------------------------------|---|
| Number Of Units In Package 1 | 1 |
|------------------------------|---|

| | |
|------------------|--------|
| Package 1 Height | 7.2 cm |
|------------------|--------|

| | |
|-----------------|--------|
| Package 1 Width | 9.6 cm |
|-----------------|--------|

| | |
|------------------|---------|
| Package 1 Length | 20.5 cm |
|------------------|---------|

| | |
|------------------|---------|
| Package 1 Weight | 171.0 g |
|------------------|---------|

Contractual warranty

| | |
|----------|-----------|
| Warranty | 24 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)